Turbofan E35 on the A26 **Electric Convection Oven** on an optional Stainless Steel Stand



6 tray capacity (oven)



Stainless steel outer




Schamel oven liner




Electronic thermostat




Plug in door seal (removable for cleaning)





Sime driven steam system







Field reversible door



Single or 3 phase (specify on ordering)

Optional stand constructed in stainless steel with rack supports S



Scastor option (stand)



E35 on the A26



Turbofan E35 on the A26

Electric Convection Oven on an optional Stainless Steel Stand

CONSTRUCTION (E35)

Top and sides stainless steel Enamel oven interior Stay cool twin pane glass door (outer surface 73°C when oven operating at 180°C) Interlocking door handle Stainless steel oven racking system with runners for wire racks Insulated all round for zero clearance left side and rear Field reversible door

CONSTRUCTION (A26)

Stainless steel frame and rack supports Strong, robust and functional Adjustable feet front and rear Supplied knocked down for assembly on site

CONTROLS

Electronic thermostat variable from 60°C to 280°C ± 1°C 1 hour bake timer with buzzer Timed water injected steam 2 speed fan (700rpm-1400rpm) On/off switch Dual direction fan High limit safety cut out

CLEANING AND SERVICING

Access to all parts from the front and right side of the unit Easy clean surfaces Fully removable oven racking system Door outer glass hinged for cleaning access

OPTIONS

Fully insulated stainless steel door with twin pane glass viewing window Stacking kits for double stacked oven installations Provers, see E85-8 / E85-12 spec sheet Trays, wire racks Stand castors

SPECIFICATIONS

Electrical Requirements

400-415V, 50Hz, 12.5kW, 3P+N+E, 17.4A/ph, 5 wire

Water

19mm (³/4") BSP thread 80psi max inlet pressure 20psi min inlet pressure

External Dimensions

Width	880mm
Height	1700mm on stand
Depth	880mm (E35-26)
Depth	980mm (E35-30)

Internal Dimensions (E35)

Width 460mm

Height 710mm Depth 660mm (E35-26)

Depth 762mm (E35-30) Oven Rack Dimensions

 Width
 460mm

 Depth
 660mm (E35-26)

 Depth
 762mm (E35-30)

Nett Weight

150kg (330lbs) E35-26 176kg (388lbs) E35-30

Packing Data (E35-26)

200kg (441lbs) 0.96m³ (33.8ft³) Width 1001mm Height 990mm Depth 965mm

Packing Data (E35-30)

226kg (498lbs) 1.04m³ (36.7ft³) Width 920mm Height 990mm Depth 1140mm

Packing Data (A26)

23kg (51lbs) 0.12m³ (4.2ft³) Width 900mm Height 920mm Depth 145mm

MOFFAT

www.moffat.com.au

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave,Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 Email vsales@moffat.com.au www.moffat.com.au

New South Wales

Telephone 02-8833 4111 Email nswsales@moffat.com.au

South Australia Telephone 08-8274 2116 Email dmiller@moffat.com.au

Queensland Telephone 07-3630 8600 Email qldsales@moffat.com.au

Western Australia Telephone 08-9305 8855 Email jberent@moffat.com.au


New Zealand Moffat Limited


Christchurch


Telephone 03-389 1007 Email sales@moffat.co.nz www.moffat.co.nz


Auckland

Telephone 09-574 3150 Email sales@moffat.co.nz











ISO 9001 All Turbofan products are designed and manufactured by Moffat Ltd using the internationally recognised ISO 9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.
Printed in New Zealand © Copyright Moffat Ltd Moffat/2725/BH/5M/01.03





880mm (E35-26)