## **Quartz Star**




## Quartz Star Upright Cabinet Bottom Mounted


## Features:


- Designed for 43°C ambient environment
- Adjustable electronic controller with digital temperature display
- High efficiency, long life LED strip lighting (lights are optional on solid door models)
- 100% CFC free polyurethane foam for greater insulation properties and added strength
- Self contained cabinet with warm air from condenser blown up the face of door to reduce condensation.
- Bottom mounted removable cassette system
- Auto defrost utilising waste heat recovery vaporiser
- Optimised ducted air flow system
- Four adjustable plastic coated shelves/door
- Triple glazed doors for higher efficiency and reduced condensation
- · Hermetique compressor

Model	QS1	QS2
Capacity	500 litres	900 litres
Finish: White Colorbond® interior and exterior with stainless steel inte	ernal floor*	
Refrigerator Glass Door +1°/+4° kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>HQS1GDCB</b> 160/3.8/620	<b>HQS2GDCB</b> 230/4.6/760
Refrigerator Solid Door +1°/+4° kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>HQS1SDCB</b> 160/3.8/620	<b>HQS2SDCB</b> 230/4.6/760
Finish: Stainless Steel interior and exterior*		
Refrigerator Glass Door +1°/+4° kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>HQS1GDSS</b> 160/3.8/620	<b>HQS2GDSS</b> 230/4.6/760
Refrigerator Solid Door +1°/+4° kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>HQS1SDSS</b> 160/3.8/620	<b>HQS2SDSS</b> 230/4.6/760

\*Refer notes page 15







989 Ga Options (see page 15):

Cylindrical



Stainless steel shelf



Gas: Self-contained fridge R134a@-5C SST Remote units R404a (others available) Electrical lead length 1.5m min. 240V 50Hz Heat rejection self-contained units: Fridge 1.4xWr

